



DN	A mm	B mm	Weight Kg
04	96	51	0.244
06	105	58.5	0.321
10	132	71	0.584
15	162	73	1.000
20	192	94	1.680

Ref.	Désignation	Num.	Material
1	BODY	1	CC491K (1)

OBSERVATION(S) :	
MAXIMUM USE CONDITIONS : 10 BAR at 180°C	
ENDS :	
ON REQUEST : 131.08 and 131.12 for 100 pieces	
REFERENCE NORMS : (1) NF EN 1982 (Copper, Alloy copper and casting)	
(2) NF EN 12164 (Copper, alloy copper cutting off)	
test P10, P11 : NF EN 12266-1 / test P20, P21 : NF EN 12266-2 (bench test)	
For compatibility of matériel, consult us	Subject to modifications

43	TUBULURE	1	CW614K (2)
42	TUBULURE NUT	1	CW614K (2)
16	PLUG	1	CC491K (1)
14	PACKING NUT	1	CW614K (2)
13	PLACKING GLAND	1	CW614K (2)
12	PACKING	1	CERAMIC GRAPHIT

Drawer: R.BOISSEAU	Sign : JP.AC
Indice : 01 of 27/12/02	
INVERTED PLUG VALVE BRONZE	REF: 131.Ø