



DN	A mm	B mm	Weight Kg
06	70	56	0.310
08	92	60	0.500
10	105	62	0.620
15	122	72	1.040
20	132	81	1.860

Ref.	Désignation	Num.	Material
1	BODY	1	CC491K (1)

<b>OBSERVATION(S) :</b>	
MAXIMUM USE CONDITIONS : 10 BAR AT 180°C	
ENDS : HEAD TOP RAIL AND NOZZLE	
ON REQUEST :	
REFERENCE NORMS : ( 1 ) NF EN 1982 (Copper, Alloy copper and casting)	
( 2 ) NF EN 12164 (Copper, alloy copper cutting off)	
test P10, P11 : NF EN 12266-1 / test P20, P21 : NF EN 12266-2 (bench test)	
For compatibility of matériel, consult us	Subject to modifications

43	NOZZLE	1	CW614K (2)
42	NOZZLE NUT	1	CW614K (2)
16	PLUG	1	CC491K (1)
14	PACKING NUT	1	CW614K (2)
13	PLACKING GLAND	1	CW614K (2)
12	PACKING	1	CERAMIC GRAPHIT

Drawer: S.GERTSCH	Sign : JP.AC.
Indice : 00 of 25/09/02	
INVERTED PLUG VALVE BRONZE	Ref . 136.Ø