



DN	A	B	D	Hmaxi	Weight
mm	mm	mm	mm	mm	Kg
15	79	65	95	150	1.450

Ref.	Désignation	Num.	Material
1a	LEVEL CONTROLLER BODY	1	CC491K (1)

OBSERVATION(S) : RANGE PN16
 MAXIMUM USE CONDITIONS : 16 BAR at 180°C (Depend of material of pipe)
 ASSEMBLING : WITH RHODOID PIPE / BOROSILICATE, PROTECTION FOR PIPE
 ENDS : ISO FLANGE NP16
 ON REQUEST : ASA FLANGE and SPECIAL DRILLING
 REFERENCE NORMS : (1) NF EN 1982 (Copper, Alloy copper and casting)
 (2) NF EN 12164 (Copper, alloy copper cutting off) NF E 29 311(dimensions of flanges)
 test P10, P11 : NF EN 12266-1 / test P20, P21 : NF EN 12266-2 (bench test)
 For compatibility of matériel, consult us Subject to modifications

45	GASKET	1	PTFE
23	SPRING	1	SPRING STEEL
19	BALL	1	BAKELITE
14b	PACKING NUT	1	CC491K (1)
13b	PACKING GLAND	1	CW614N (2)
13a	PACKING GLAND	1	CW614N (2)
12	PACKING	1	GRAPHITE + FIBER
7	STEM	1	CW614N (2)
5	DISC HOLDER	1	CW614N (2)
4	DISC	1	FPM

Drawer: M.FONTAINE	Sign : M.F.
Indice : 03 of 03/05/10	
BRONZE VISUAL LEVEL CONTROLLER	Ref: 2276PIØ