



DN	A mm	B mm	D mm	H mm	Weight Kg
15	79	65	95	103	1.200

Ref.	Désignation	Num.	Material
1	BODY	1	CC491K (1)

OBSERVATION(S) : RANGE PN16  
 MAXIMUM USE CONDITIONS : 16 BAR at 180°C (Depend of material of pipe)  
 ASSEMBLING : WITH RHODOID PIPE / BOROSILICATE, PROTECTION FOR PIPE  
 ENDS : ISO FLANGE  
 ON REQUEST : ASA FLANGE and SPECIAL DRILLING  
 REFERENCE NORMS : ( 1 ) NF EN 1982 (Copper, Alloy copper and casting)  
 ( 2 ) NF EN 12164 (Copper, alloy copper cutting off) NF E 29 311 (flanges)  
 test P10, P11 : NF EN 12266-1 / test P20, P21 : NF EN 12266-2 (bench test)  
 For compatibility of matériel, consult us Subject to modifications

Drawer: S.GERTSCH	Sign : JP.AC.
Indice : 01 of 31/12/02	

45	GASKET	1	PTFE
37	PLUG	1	CW614N (2)
14b	PACKING NUT	1	CC491K (1)
13b	PACKING GLAND	1	CW614N (2)

BRONZE VISUAL LEVEL CONTROLLER	Ref: 2276PSØ
-----------------------------------	--------------