



DN	A mm	B mm	C mm	O	Weight Kg
08	49	35	80	G1/4	0.220
12	55	38	80	G3/8	0.275
15	70	54	102	G1/2	0.473
20	80	62	117	G3/4	0.651
26	90	70	130	G1"	0.992
33	105	82	150	G1"1/4	1.603
40	120	88	170	G1"1/2	2.352
50	140	96	176	G2"	3.415

Ref.	Désignation	Num.	Material
1	BODY	1	CC491K (1)

OBSERVATION(S) :
 MAXIMUM USE CONDITIONS : AIR : 10BARS AT 80°C
 ENDS : GAZ THREADS
 ON REQUEST : NPT THREADS
 REFERENCE NORMS : (1) NF EN 1982 (Copper, Alloy copper and casting)
 (2) NF EN 12164 (Copper, alloy copper cutting off)
 test P10, P11 : NF EN 12266-1 / test P20, P21 : NF EN 12266-2 (bench test)
 For compatibility of matériel, consult us Subject to modifications

Drawer: R.BOISSEAU
 Indice : 01 of 26/12/02 Sign : JP.AC.

INVERTED PLUG VALVE
 BRONZE
 Ref: 253.φ

37	PLUG	1	CC491K (1)
23	SPRING	1	WORK STEEL
19	HANDLE	1	CAST
16	PLUG	1	CC491K (1)