



DN	A mm	B mm	C mm	O	Weight Kg
08	53	35	80	G1/4	0.220
12	59	38	80	G3/8	0.280
15	75	54	102	G1/2	0.460
20	85	62	117	G3/4	0.620
26	95	70	130	G1"	1.020
33	110	82	150	G1 1/4	1.600

Ref.	Désignation	Num.	Material
1	BODY	1	CC491K (1)

OBSERVATION(S) :	
MAXIMUM USE CONDITIONS : AIR : 10 BARS AT 80°C	
ENDS : GAZ THREADS	
ON REQUEST : NPT THREADS	
REFERENCE NORMS : (1) NF EN 1982 (Copper, Alloy copper and casting)	
(2) NF EN 12164 (Copper, alloy copper cutting off)	
test P10, P11 : NF EN 12266-1 / test P20, P21 : NF EN 12266-2 (bench test)	
For compatibility of matériel, consult us	Subject to modifications

Drawer: R.BOISSEAU	Sign : JP.AC
Indice : 01 of 26/12/02	

INVERTED PLUG VALVE BRONZE	Ref: 254.φ
-------------------------------	------------

37	PLUG	1	CC491K (1)
23	SPRING	1	WORK STEEL
19	HANDLE	1	CAST
16	PLUG	1	CC491K (1)