



DN	A mm	B mm	D mm	H mm	Weight Kg
15	80	10	95	110	1.350
20	95	15	105	130	1.900
25	130	20	115	170	3.350

Ref.	Désignation	Num.	Material
1a	BODY	1	CC491K (1)

OBSERVATION(S) : RANGE PN16  
 MAXIMUM USE CONDITIONS : 16 BAR at 205°C  
 ASSEMBLING : WITH RHODOID PIPE / BOROSILICATE, PROTECTION FOR PIPE  
 ENDS : ISO FLANGE  
 ON REQUEST : ASA FLANGE and SPECIAL DRILLING  
 REFERENCE NORMS : ( 1 ) NF EN 1982 (Copper, Alloy copper and casting)  
 ( 2 ) NF EN 12164 (Copper, alloy copper cutting off) NF E 29 311 (flanges)  
 test P10, P11 : NF EN 12266-1 / test P20, P21 : NF EN 12266-2 (bench test)  
*For compatibility of matériel, consult us* *Subject to modifications*

45	GASKET	2	PTFE
37	PLUG	2	CW614N (2)
16	PLUG	1	CC491K (1)
14b	PACKING NUT	1	CC491K (1)
14a	PACKING NUT	1	CW614N (2); CC491K (1) DN25
13b	PACKING GLAND	1	CW614N (2)
13a	PACKING GLAND	1	CW614N (2); CC491K (1) DN25
12	PACKING	1	PTFE

Drawer: VAILLANT	Sign : JPAC
Indice : 03 of 11/05/05	
BRONZE VISUAL LEVEL CONTROLLER	Ref: 276PSØ