



AUTEXIER

MANUFACTURER OF INDUSTRIAL VALVES

93 Rue Louis Blanc - 02300 CHAUNY - FRANCE
 Phone : +33 (0)3 23 52 02 86 Fax : +33 (0)3 23 39 52 28
 Website : www.autexier.fr

Ref. AUR3 Family : 40

Rev. 03

Date : 15 Dec. 2021

Page 1/1

SYMETRICAL FITTING WITH ALUMINIUM-BRONZE NATO FLANGE

Ref. AUR3V

SERIES :

- AUR3

For material compatibility, contact us

CARACTERISTICS :

- PN16 (Nominal Pressure)
- ENDS : NATO Flange / Symmetrical fitting with lock
- MATERIAL : ALUMINIUM BRONZE CC333G

MAXIMUM CONDITIONS OF USE :

- 16 bar of -10°C to 100°C

APPLICATIONS :

- Water-based fluids
- Steam (8 bar)
- Seawater



Subject to modifications

DIMENSIONS


REF.	AUR3.65V	AUR3.66V
NATO	6"1/2	7"1/2
DN	65	65
A (mm)	165	190,5
B (mm)	133	159
C (mm)	108	133,5
L (mm)	142	142

NOMENCLATURE

Rep	Qty	Designation	Material
37	1	PLUG	BRONZE / BRASS
45	1	BLACK GASKET	NBR
54	1	FEMALE THEADED FLANGE	ALUMINIUM BRONZE
68	1	CHAIN	STAINLESS STEEL
69	1	MALE FITTING	BRONZE

REFERENCES NORMS :

- Material : NF EN 1982 - NF EN 12163 - NF EN 12164 - NF EN 10272
- Testing & checking : NF EN 12266-1/-2 (bench test)



Ref. instruction of assembling : -

Ref. instruction of operation : -

Mounting & assembly guides are available on our website.

These data are for information and can be modified without notice. It is not up to us to appreciate specifications. It is up to the customer to verify the adequacy between the equipment chosen and the real conditions of use.