



189/189T & 189BP				
Ø-DN	15	20	25	32
B	74	85	100	122
C	30	35	40	45
H	28	35	39	43
Kg	0,35	0,56	0,9	1,4

189/189Tø.ø & 189.ø.øBP				
Ø-DN	15/20	20/25	25/32	32/40
B	74	85	100	122
C	44	53	59	64
H	28	35	39	43
Kg	0,39	0,61	1,1	1,55

CONCEPTION

Bronze - CuSn5ZnPb / ASTM B62

Clapet FPM : Réf. 189 -15°C / +200°C

Clapet PTFE : Réf. 189T -50°C / +225°C

Clapet Silicone : Réf. 189BP -50°C / +200°C

Entrée Mâle / Sortie Femelle

Orifices décalés 189 / 189Tø.ø

APPLICATIONS

Eau chaude & Fluides Industriels

Fluides aqueux

Vapeur basse pression (8 Bar)

Gaz neutres (air comprimé,...)

OPTIONS

Nickel / Chromage

Clapet dégraissé

Connexion à brides ou NPT



PMS/MSP : 40 Bar

FPM Disc : Ref. 189 -15°C / +200°C

PTFE Disc : Ref. 189T -50°C / +225°C

Silicone Disc : Ref. 189BP -50°C / +200°C

Male inlet / Female outlet

Different size in outlet 189 / 189Tø.ø

Hot water & Industrial fluids

Water-based fluids

Low pressure steam (8 Bar)

Neutral gases (air compressed, ...)

Nickel / Chrome plating

Degreased disc / seat

Flanges or NPT connection