



Ø-DN	12/20	15/26	20/33	26/40	33/50
A	26	32	40	49	57
B	30	36	46,5	53	57
C	126	130	158	183	225
Kg	0,58	0,73	1,9	1,9	2,6

CONCEPTION

Bronze - CuSn5ZnPb / ASTM B62

PMS/MSP : 40 Bar

Clapet FPM : Réf. 471 -15°C / +200°C

FPM Disc : Ref. 471 -15°C / +200°C

Clapet PTFE : Réf. 471T -50°C / +225°C

PTFE Disc : Ref. 471T -50°C / +225°C

Clapet Silicone : Réf. 471BP -50°C / +200°C

Silicone Disc : Ref. 471BP -50°C / +200°C

Orifices décalés

Different size in outlet

Entrée / Sortie Femelle

Female Inlet / Outlet

Ressort Acier inox

Stainless steel spring

Avec système de relevage

With handlever

Vis de purge de condensation

Drain tap screw

APPLICATIONS

Eau chaude & Fluides Industriels

Hot water & Industrial fluids

Fluides aqueux

Water-based fluids

Vapeur moyenne pression (13 Bar)

Medium-pressure steam (13 Bar)



OPTIONS

Nickelage / Chromage

Nickel / Chrome plating

Connexion à brides (472) ou NPT

Flanges (472) or NPT connection

Mâle / Mâle

Male / Male