



Code	0	1	2	3	4	5	6	7	8	9
B	75	95	120	145	170	200	230	260	300	320
C	74	74	74	74	74	74	74	74	74	74
F	115	135	160	185	210	240	270	300	340	355
O	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Kg	1,81	1,9	2,25	3	3,43	3,5	4,05	4,1	5,18	5,36

### CONCEPTION

Bronze - CuSn5ZnPb / ASTM B62

Raccordement Femelle / Femelle

Glacé Polyprismatique

Glaces et joints compris

PMS/MSP : 16 Bar

TMS/MST : 225°C

Female / Female

Reflex glass indicator

Glass and packing included

### APPLICATIONS

Fluides aqueux (16 Bar)

Huiles & hydrocarbures

Vapeur saturée (13 Bar)



Water-based fluids (16 Bar)

Oil & Gas

Saturated steam (13 Bar)

### OPTIONS

Étanchéité spéciale hydrocarbures

Montage multiple avec intermédiaire

Réf. C2800.15

Connexions par tubulures Réf. CTUB.Ø

Tightness packing special Oil & Gas

Several mountings with intermediate connection

Ref. C2800.15

Tube connections Ref. CTUB.Ø