



Ø-DN	12	15	20	25	32	40	50	60	80
A	55	60	65	75	87	95	110	126	156
D	3/8"	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"
H	37	43	47	51	60	63	75	85	116
Kg	0,2	0,35	0,45	0,62	0,94	1,36	2	3,1	5

CONCEPTION

Bronze - CuSn5ZnPb / ASTM B62 Réf. 109Ø
 Cupro-Aluminium - CuAl9Ni3Fe2 Réf. AU109Ø
 Cupro-Nickel - CuNi10Fe1Mn1 Réf. AN109.Ø
 Femelle / Femelle - Chapeau vissé
 Contact Bronze / Bronze Réf. 109M
 Contact Bronze / FPM Réf. 109B
 Internes bronze Réf. 109B ou MØTB

PMS/MSP : 20 Bar

TMS/MST : -15°C / +200°C

Bronze - CuSn5ZnPb / ASTM B62 Ref. 109Ø
 Aluminium Bronze - CuAl9Ni3Fe2 Ref. AU109Ø
 Copper-Nickel - CuNi10Fe1Mn1 Ref. AN109.Ø
 Female / Female - Screwed bonnet
 Contact Bronze / Bronze Ref. 109M
 Contact Bronze / FPM Ref. 109B
 Bronze trim Ref. 109B ou MØTB

APPLICATIONS

Fluides aqueux
 Eau de mer



Water-based fluids
 Seawater

OPTIONS

Tarudage NPT / API

NPT / API connection