



DN	32	40	50	65	80	100
A	54	58	62	72	94	108
B	73	80	100	112	126	150
C	33	33	43	46	46	52
H	144	147	157	172	205	216
L	165	165	165	165	218	218
Embase ISO Base ISO	F05	F05	F05	F05	F07	F07
Kg	2,200	-	3,050	5,900	6,965	7,900

CONCEPTION

Bronze - CuSn5ZnPb / ASTM B62
 Cupro-Aluminium - CuAl9Ni3Fe2
 Corps et Papillon Bronze Réf. A601
 Corps et Papillon Cupro-Aluminium Réf. AU601
 Raccordement bride ISO PN10 / PN16 / PN20

APPLICATIONS

Fluides aqueux
 Eau
 Eau de mer Réf. AU601

OPTIONS

Manchette EPDM, FPM ou NBR
 Réducteur (A601MØ / AU601MØ)



PMS/MSP : 16 Bar

TMS/MST : -15°C / +100°C

Bronze - CuSn5ZnPb / ASTM B62
 Aluminium Bronze - CuAl9Ni3Fe2
 Body & Wedge disc in Bronze Ref. A601
 Body & Wedge disc in Aluminium Bronze Ref. AU601
 Junction ISO flange PN10 / PN16 / PN20

Water-based fluids
 Water
 Seawater Ref. AU601

EPDM, FPM or NBR Cuff
 Gearbox (A601M / AU601MØ)