



DN	32	40	50	65	80	100	125	150	200	250
A	54	58	62	72	94	108	124	134	170	206
B	73	80	100	112	126	150	181	209	257	330
C	33	33	43	46	46	52	56	56	60	68
H	160	163	173	188	212	222	235	247	304	351
H2	184	187	197	212	235	245	258	270	328	471
V	100	100	100	100	100	125	125	160	160	200
Embase ISO Base ISO	F05	F05	F05	F05	F07	F07	F07	F07	F07	F10
Kg	4,600	-	5,400	6,100	6,910	7,900	10,160	13,900	-	31,300

CONCEPTION

Bronze - CuSn5ZnPb / ASTM B62
 Cupro-Aluminium - CuAl9Ni3Fe2
 Corps et Papillon Bronze Réf. A601M
 Corps et Papillon Cupro-Aluminium Réf. AU601M
 Raccordement bride ISO PN10 / PN16 / PN20

PMS/MSP : 16 Bar

TMS/MST : -15°C / +100°C

Bronze - CuSn5ZnPb / ASTM B62
 Aluminium Bronze - CuAl9Ni3Fe2
 Body & Wedge disc in Bronze Ref. A601M
 Body & Wedge disc in Aluminium Bronze Ref. AU601M
 Junction ISO flange PN10 / PN16 / PN20

APPLICATIONS

Fluides aqueux
 Eau
 Eau de mer Réf. AU601M

Water-based fluids
 Water
 Seawater Ref. AU601M

OPTIONS

Manchette EPDM, FPM ou NBR

EPDM, FPM or NBR Cuff

