



DN	32	40	50	65	80	100
A	53	56	62	69	94	108
B	78	76	100	108	124	150
C	33	33	43	46	43	52
D	4xM16	4xM16	4xM16	4xM16	8xM16	8xM16
E	100	110	125	145	160	180
H	144	147	157	172	205	216
L	165	165	165	165	218	218
Embase ISO Base ISO	F05	F05	F05	F05	F07	F07
Kg	-	2,960	3,850	4,530	-	-

CONCEPTION

Bronze - CuSn5ZnPb / ASTM B62
 Cupro-Aluminium - CuAl9Ni3Fe2
 Corps et Papillon Bronze Réf. A602
 Corps et Papillon Cupro-Aluminium Réf. AU602
 Raccordement bride ISO PN10 / PN16

APPLICATIONS

Fluides aqueux
 Eau
 Eau de mer Réf. AU602

OPTIONS

Raccordement bride ISO PN20
 Manchette EPDM, FPM ou NBR
 Réducteur (A602MØ / AU602MØ)



PMS/MSP : 16 Bar

TMS/MST : -15°C / +100°C

Bronze - CuSn5ZnPb / ASTM B62
 Aluminium Bronze - CuAl9Ni3Fe2
 Body & Wedge disc in Bronze Ref. A602
 Body & Wedge disc in Aluminium Bronze Ref. AU602
 Junction ISO flange PN10 / PN16

Water-based fluids
 Water
 Seawater Ref. AU602

Junction ISO flange PN20
 EPDM, FPM or NBR Cuff
 Gearbox (A602M / AU602MØ)