



DN	32	40	50	65	80	100	125	150	200	250
A	53	56	62	69	95	103	117	133	170	208
B	78	85	105	108	129	150	183	210	257	330
C	33	33	43	46	46	52	56	56	60	68
D	4xM16	4xM16	4xM16	4xM16	8xM16	8xM16	8xM16	8xM20	12xM20	12xM24
E	100	110	125	145	160	180	210	240	295	355
H	160	163	173	188	212	222	235	247	304	351
H2	184	187	197	212	235	245	258	270	328	471
V	100	100	100	100	100	125	125	160	160	200
Embase ISO Base ISO	F05	F05	F05	F05	F07	F07	F07	F07	F07	F10
Kg	5,000	-	6,150	6,970	-	10,570	14,100	15,350	21,940	41,790

### CONCEPTION

Bronze - CuSn5ZnPb / ASTM B62  
 Cupro-Aluminium - CuAl9Ni3Fe2  
 Corps et Papillon Bronze Réf. A602M  
 Corps et Papillon Cupro-Aluminium Réf. AU602M  
 Raccordement bride ISO PN10 / PN16

PMS/MSP : 16 Bar

TMS/MST : -15°C / +100°C

Bronze - CuSn5ZnPb / ASTM B62  
 Aluminium Bronze - CuAl9Ni3Fe2  
 Body & Wedge disc in Bronze Ref. A602M  
 Body & Wedge disc in Aluminium Bronze Ref. AU602M  
 Junction ISO flange PN10 / PN16

### APPLICATIONS

Fluides aqueux  
 Eau  
 Eau de mer Réf. AU602M



Water-based fluids  
 Water  
 Seawater Réf. AU602M

### OPTIONS

Raccordement bride ISO PN20  
 Manchette EPDM, FPM ou NBR

Junction ISO flange PN20  
 EPDM, FPM or NBR Cuff