



	49						50									
Ø-DN	15	20	25	32	40	50	8	12	15	20	25	32	40	50	65	80
A	59	68	83	95	108	131	51	51	70	80	90	105	117	140	153	205
B	55	67	79	95	103	120	49	49	68	78	90	102	110	131	143	170
C	14	12	17	16	23	29	9	12	14	16	17	19	23	29	38	44
O	1/2"	3/4"	1"	1"1/4	1"1/2	2"	1/4"	3/8"	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"
Kg	0,35	0,56	1	1,9	2,4	3,6	0,3	0,5	0,7	0,9	1	2	3	4,7	8	14

CONCEPTION

Bronze - CuSn5ZnPb / ASTM B62

Deux voies Femelle / Femelle

Lumière droite

Presse étoupe boulonné

PMS/MSP : 10 Bar

TMS/MST 49 : -45°C / +180°C

TMS/MST 50 : -45°C / +225°C

Bronze - CuSn5ZnPb / ASTM B62

Two-way Female / Female

Straight light / port

Bolted stuffing box

APPLICATION

Bitume

Fluides aqueux

Huiles, hydrocarbures, peintures, adhésifs

Asphalt

Water-based fluids

Oil & Gas, paintings, adhesives

OPTIONS

Tarudage NPT / API

Clé sur demande



NPT / API connection

Handlever square on request