



	130					135			
Ø-DN	4	6	10	15	20	6	10	15	20
Filetage Thread	8/13- 12/17	12/17- 15/21	15/21- 20/27	20/27	26/34	12/17- 15/21	15/21- 20/27	20/27	26/34
Douille Socket	17	21	27	30	34	21	27	30	34
A	68	74	95	121	141	56	71	76	96
B	52	59	69	75	95	83	107	141	172
Kg	0,2	0,3	0,5	0,9	1,5	0,3	0,5	1	1,6

	131					136			
Ø-DN	4	6	10	15	20	8	10	15	20
Filetage Thread	8/13- 12/17	12/17- 15/21	15/21- 20/27	20/27	26/34	15/21	15/21- 20/27	20/27	26/34
Douille Socket	17	21	27	30	34	21	27	30	34
A	96	105	132	162	192	92	105	122	132
B	51	59	71	73	94	60	62	72	81
Kg	0,25	0,32	0,6	1	1,7	0,5	0,6	1	1,9

CONCEPTION

Bronze - CuSn5ZnPb / ASTM B62

Bec droit sans tubulure

Réf. 130

Bec courbé sans tubulure

Réf. 135

Bec droit avec tubulure

Réf. 131

Bec courbé avec tubulure

Réf. 136

PMS/MSP : 16 Bar

TMS/MST : -45°C / +225°C

Bronze - CuSn5ZnPb / ASTM B62

Straight nozzle without drain tube

Ref. 130

Curved nozzle without drain tube

Ref. 135

Straight nozzle with drain tube

Ref. 131

Curved nozzle with drain tube

Ref. 136

APPLICATIONS

Huiles, hydrocarbures, peintures, adhésifs

Fluides aqueux

Oil & Gas, paintings, adhesives

Water-based fluids

OPTIONS

Taraudage NPT / API



NPT / API connection