



52.Ø

53L ou/or T.Ø

52									53							
Ø-DN	15	20	25	32	40	50	65	80	15	20	25	32	40	50	65	80
A	90	100	115	130	150	170	210	230	130	145	158	183	200	220	250	265
B	70	80	85	103	110	135	150	175	70	80	85	103	110	135	150	175
C	14	16	17	19	23	29	38	44	14	16	17	19	23	29	38	44
D	95	105	115	140	150	165	185	200	95	105	115	140	150	165	185	200
Kg	2,3	3,4	4,4	7,3	9,2	13	18	26	2,6	3,7	4,7	7,6	9,7	13,4	20,4	27,5

CONCEPTION

Bronze - CuSn5ZnPb / ASTM B62

Deux voies

Trois voies lumière en T ou en L

Presse étoupe boulonné

Réf. 52

Réf. 53

PMS/MSP : 16 Bar

TMS/MST : -45°C / +225°C

Bronze - CuSn5ZnPb / ASTM B62

Two-way

Three-way T or L port

Bolted stuffing box

Ref. 52

Ref. 53

APPLICATION

Bitume

Fluides aqueux

Huiles, hydrocarbures, peintures, adhésifs

Asphalt

Water-based fluids

Oil & Gas, paintings, adhesives

OPTIONS

Taraudage NPT / API

Clé sur demande



NPT / API connection

Handlever square on request