



Ø-DN	251				252							
	20/12	26/15	33/20	40/26	15/12	20/15	26/20	33/20	33/26	40/26	40/33	
OA	3/4"	1"	1"1/4	1"1/2	1/2"	3/4"	1"	1"1/4	1"1/4	1"1/2	1"1/2	
OD	3/8"	1/2"	3/4"	1"	3/8"	1/2"	3/4"	3/4"	1"	1"	1/4"	
B	80	98	108	126	64	78	88	92	100	100	120	
C	55	72	83	96	48	60	65	65	75	75	95	
Kg	0,9	1,6	2,2	3,3	0,7	1	1,4	1,5	2,2	2,2	3,6	

CONCEPTION

Bronze - CuSn5ZnPb / ASTM B62

1 entrée / 3 sorties

Réf. 251

1 entrée / 2 sorties

Réf. 252

Ressort de rattrapage d'usure

PMS/MSP : 6 Bar

TMS/MST : -45°C / +225°C

Bronze - CuSn5ZnPb / ASTM B62

1 Inlet / 3 Outlets

Ref. 251

1 Inlet / 2 Outlets

Ref. 252

Wear ajustment spring

APPLICATIONS

Air comprimé

Gaz non-toxiques



Compressed Air

Non-toxic gases

OPTIONS

Taroudage NPT / API

NPT / API connection