



	121					122					123				
Ø-DN	4	6	10	15	20	4	6	10	15	20	4	6	10	15	20
Filetage Thread	8/13- 12/17	12/17- 15/21	15/21- 20/27	20/27	26/34	8/13- 12/17	12/17- 15/21	15/21- 20/27	20/27	26/34	8/13- 12/17	12/17- 15/21	15/21- 20/27	20/27	26/34
Douille Socket	17	21	27	30	34	17	21	27	30	34	17	21	27	30	34
A	63	72	86	110	123	77	85	100	128	143	90	97	130	148	169
B	40	56	62	72	81	37	56	62	71	81	42	50	63	72	82
Kg	0,15	0,21	0,41	0,75	1,15	0,16	0,22	0,45	0,84	1,2	0,2	0,28	0,5	0,9	1,2

CONCEPTION

Bronze - CuSn5ZnPb / ASTM B62

Bec droit sans tubulure

Réf. 121

Bec courbé sans tubulure

Réf. 122

Bec droit avec tubulure

Réf. 123

PMS/MSP : 10 Bar

TMS/MST : -45°C / +225°C

Bronze - CuSn5ZnPb / ASTM B62

Straight nozzle without drain tube

Ref. 121

Curved nozzle without drain tube

Ref. 122

Straight nozzle with drain tube

Ref. 123

APPLICATIONS

Fluides aqueux

Huiles, hydrocarbures, peintures, adhésifs

Water-based fluids

Oil & Gas, paintings, adhesives

OPTIONS

Taraudage NPT / API



NPT / API connection