



DN	15	20	25	32	40	50	65	80	100	125	150	200
B	STANDARD PN16, AUTRES DIMENSIONS SUR DEMANDE / ON REQUEST											
C-Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"	5"	6"	8"
D	STANDARD PN16, AUTRES DIMENSIONS SUR DEMANDE											
E	STANDARD PN16, OTHER DIMENSIONS ON REQUEST											

CONCEPTION

Bronze - CuSn5ZnPb / ASTM B62

Bride taraudée Réf. BØ.Ø
 Bride filetée Réf. BFØ.Ø

Cupro-Aluminium - CuAl9Ni3Fe2

Bride taraudée Réf. AUBØ.Ø
 Bride filetée Réf. AUBFØ.Ø

Cupro-Nickel - CuNi10Fe1Mn1

Bride taraudée Réf. ANBØ.Ø
 Bride filetée Réf. ANBFØ.Ø

PMS/MSP : 20 Bar

TMS/MST : -50°C / + 250°C

Bronze - CuSn5ZnPb / ASTM B62

Female threaded flange Ref. BØ.Ø
 Male threaded flange Ref. BFØ.Ø

Aluminium Bronze - CuAl9Ni3Fe2

Female threaded flange Ref. AUBØ.Ø
 Male threaded flange Ref. AUBFØ.Ø

Copper-Nickel - CuNi10Fe1Mn1

Female threaded flange Ref. ANBØ.Ø
 Male threaded flange Ref. ANBFØ.Ø

APPLICATIONS

Fluides aqueux
 Vapeur (8 Bar)
 Eau de mer



Water-based fluids
 Steam (8 Bar)
 Seawater

OPTIONS

Perçage spécial
 Embouts lisses
 Embouts à souder

Special drilling
 Smooth finish ends
 Socket welding