



AUTEXIER

MANUFACTURER OF INDUSTRIAL VALVES

93 Rue Louis Blanc - 02300 CHAUNY - FRANCE
Phone : +33 (0)3 23 52 02 86 Fax : +33 (0)3 23 39 52 28
Website : www.autexier.fr

Ref. AU591 Family: 09

Rev. 10

Date : 28 July 2020

Page 1/2

ALUMINIUM-BRONZE DOUBLE WEDGE GATE VALVE WITH FLANGES Ref. AU591.Ø

SERIES :

- AU591

For material compatibility, contact us

CARACTERISTICS :

- PN16 (Nominal Pressure)
- ENDS : Flanges ISO PN10 or PN16
- MATERIAL : ALUMINIUM BRONZE CC333G

MAXIMUM CONDITIONS OF USE :

- 16 bar of -10°C to 150°C


APPLICATIONS :

- Seawater
- Water-based fluids
- Steam (8 bar)

OPTIONS :


- Special drilling
- Face to face

Specific dimensions, contact us



Subject to modifications

NOMENCLATURE			
Rep	Qty	Designation	Material
1	1	BODY	ALUMINIUM BRONZE
2	1	BONNET	ALUMINIUM BRONZE
3	1	DOUBLE WEDGE DISC	ALUMINIUM BRONZE
7	1	STEM	ALUMINIUM BRONZE
8	1	HANDWHEEL	EPOXY COATED ZAMAK
10	1	STEM NUT	ALUMINIUM BRONZE
11	1	WEDGE DISC NUT	ALUMINIUM BRONZE
12	1	PACKING	PTFE
17	1	PACKING FLANGE	ALUMINIUM BRONZE
34	1	GUIDE	ALUMINIUM BRONZE
38a	6	SCREW	STAINLESS STEEL
38b	2	SCREW	STAINLESS STEEL
40	4	NUT	STAINLESS STEEL
41	9	WASHER	STAINLESS STEEL
45	1	O-RING	FPM
77	1	TRAVEL INDICATOR	ALUMINIUM BRONZE



REFERENCES NORMS :

- Material: NF EN 1982 - NF EN 12163 - NF EN 12164 - NF EN 10272
- Testing & checking : NF EN 12266-1/-2 (bench test)
- Face to face: NF EN 558 - Series 29

Ref. instruction of assembling : 0904DA123E

Ref. instruction of operation : 0904DA087E

**Mounting & assembly guides are available
on our website.**

DIMENSIONS							
DN	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	H (mm)	Weight (Kg)
40	136	110	110	150	18	220	7.650
50	142	110	125	165	18	230	9.760

These data are for information and can be modified without notice. It is not up to us to appreciate specifications. It is up to the customer to verify the adequacy between the equipment choosen and the real conditions of use.



AUTEXIER

MANUFACTURER OF INDUSTRIAL VALVES

93 Rue Louis Blanc - 02300 CHAUNY - FRANCE
Phone : +33 (0)3 23 52 02 86 Fax : +33 (0)3 23 39 52 28
Website : www.autexier.fr

Ref. AU591 Family: 09

Rev. 10

Date : 28 July 2020

Page 2/2

ALUMINIUM-BRONZE DOUBLE WEDGE GATE VALVE WITH FLANGES Ref. AU591.Ø

SERIES :

- AU591

For material compatibility, contact us



CARACTERISTICS :

- PN16 (Nominal Pressure)
- ENDS : Flanges ISO PN10 or PN16
- MATERIAL : ALUMINIUM BRONZE CC333G

MAXIMUM CONDITIONS OF USE :

- 16 bar of -10°C to 150°C (DN65)
- 16 bar of -10°C to 100°C (DN80 to DN200)


APPLICATIONS :

- Seawater
- Water-based fluids
- Steam (8 bar)

OPTIONS :


- Special drilling
- Face to face

Specific dimensions, contact us



Subject to modifications

NOMENCLATURE			
Rep	Qty	Designation	Material
1	1	BODY	ALUMINIUM BRONZE
2	1	BONNET	ALUMINIUM BRONZE
3	1	DOUBLE WEDGE DISC	ALUMINIUM BRONZE
7	1	STEM	ALUMINIUM BRONZE
8	1	HANDWHEEL	EPOXY COATED STEEL
11	1	WEDGE DISC NUT	ALUMINIUM BRONZE
12	m	PACKING	GRAPHITE + FIBER
13	1	PACKING GLAND	ALUMINIUM BRONZE
17	1	PACKING FLANGE	ALUMINIUM BRONZE
34	1	GUIDE	ALUMINIUM BRONZE
38	n	SCREW	STAINLESS STEEL
40	6	NUT	STAINLESS STEEL
41	o	WASHER	STAINLESS STEEL
45a	1	GASKET	ELASTOMER FIBER
45b	1	FLAT GASKET (65) / O-RING (80;200)	ELASTOMER FIBER (65) / NBR (80;200)
73	2	STUD	STAINLESS STEEL
77	1	TRAVEL INDICATOR	ALUMINIUM BRONZE
87	1	PACKING BOX	ALUMINIUM BRONZE



REFERENCES NORMS :

- Material : NF EN 1982 - NF EN 12163 - NF EN 12164 - NF EN 10272
- Testing & checking : NF EN 12266-1/-2 (bench test)
- Face to face: NF EN 558 - Series 29

Ref. instruction of assembling : 0904DA123E

Ref. instruction of operation : 0904DA087E

**Mounting & assembly guides are available
on our website.**

DIMENSIONS										
DN	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	H (mm)	m	n	o	Weight (Kg)
65	154	150	145	185	18	270	4	8	13	13.000
80	160	150	160	200	18	300	3	8	13	19.250
100	172	175	180	220	18	335	3	8	13	24.000
125	186	175	210	250	18	390	3	9	14	32.000
150	200	200	240	285	22	452	3	10	15	43.000
200	228	225	295	340	22	535	4	10	15	63.000

These data are for information and can be modified without notice. It is not up to us to appreciate specifications. It is up to the customer to verify the adequacy between the equipment choosen and the real conditions of use.