



AUTEXIER

MANUFACTURER OF INDUSTRIAL VALVES

93 Rue Louis Blanc - 02300 CHAUNY - FRANCE
 Phone : +33 (0)3 23 52 02 86 Fax : +33 (0)3 23 39 52 28
 Website : www.autexier.fr

Ref. 480 Family : 27

Rev. 07

Date : 18 Sept. 2023

Page 1/1

BRONZE SAFETY VALVE

Ref. 480.Ø / 480MØ / 480TØ / 480BPØ

SERIES :

- 480M : Bronze Disc
 - 480T : PTFE Disc
 - 480 : FPM Disc
 - 480BP : Silicone Disc (low pressure)
 - Female inlet / free outlet
- For material compatibility, contact us

CARACTERISTICS :

- PN40 (Nominal Pressure)
- ENDS : Female GAZ threads
- MATERIAL : BRONZE CC491K

MAXIMUM CONDITIONS OF USE :

- Ref. 480M : 40 bar of -50°C to 225°C
- Ref. 480T : 40 bar of -50°C to 225°C
- Ref. 480 : 40 bar of -15°C to 200°C
- Ref. 480BP : 40 bar of -50°C to 200°C

APPLICATIONS :

- Compressed air
- Non-toxic
- Oxygen


OPTIONS :

- NPT connection
- Flange connection
- Degreased disc


Specific dimensions, contact us




Subject to modifications




480T: DN08 to 15 and 80
480.80 / 480.80BP



480.Ø / 480BPØ DN08 to 25



480MØ



480T : DN20 to 65
480 / 480BP: DN32 to 65

NOMENCLATURE

Rep	Qty	Designation	Material
4	1	DISC	480M:BRONZE / 480T:PTFE 480:FPM / 480BP:Silicone
5	1	DISC HOLDER	BRASS/BRONZE(DN32 to 80)
6	1	SEAT	BRASS(DN08 & 12)/BRONZE
22	1	LANTERN	BRONZE
23	1	SPRING	STAINLESS STEEL
24	1	ADJUSTING SCREW	BRASS
25	1 / 2	CARRIER	BRASS/BRONZE(480T & 480 DN65 to 80)
27	1	NEEDLE	BRASS
27a	1	TIP NEEDLE	BRASS (DN32 to 80)
38	1	SCREW (DN08 to 25)	STAINLESS STEEL
39	1	FIN	BRONZE (DN32 to 80)
40	1	NUT	BRASS

REFERENCES NORMS :

- Material : NF EN 1982 - NF EN 12163 - NF EN 12164 - NF EN 10272
- Testing & checking : NF EN 12266-1/-2 (bench test)

Ref. instruction of assembling : 0904DA091E

Ref. instruction of operation : 0904DA154E

Mounting & assembly guides are available on our website.

DIMENSIONS

DN	08	12	15	20	25	32	40	50	65	80
A (mm)	14.4	14.4	18	19	21	22	23	27	32	34
B Masi (mm)	102	103	133	157	173	214	235	282	307	360
O	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"
Weight (Kg) Ref. 480	0.180	0.180	0.311	0.616	1.105	1.546	2.125	3.370	4.415	8.020

These data are for information and can be modified without notice. It is not up to us to appreciate specifications. It is up to the customer to verify the adequacy between the equipment chosen and the real conditions of use.