



DISPONIBLE À LA VENTE JUSQU'À ÉPUISEMENT DES STOCKS / AVAILABLE FOR SALE WHILE STOCK LASTS

Ø-DN	8	12	15	20	25	32	40	50
A (34)	40	45	50	60	70	85	100	115
A (36)	45	50	55	65	75	-	-	-
B	27	32	37	45	55	70	76	93
C	9	12	14	16	17	19	23	29
O	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Kg	0,1	0,16	0,22	0,38	0,56	0,9	1,4	2,2

CONCEPTION

Bronze - CuSn5ZnPb / ASTM B62

2 Voies extrémités Femelle / Femelle Réf. 34

2 Voies extrémités Mâle / Femelle Réf. 36

PMS/MSP : 10 Bar

TMS/MST : -45°C / +225°C

Bronze - CuSn5ZnPb / ASTM B62

2 ways : Female / Female threaded ends Ref. 34

2 ways : Male / Female threaded ends Ref. 36

APPLICATIONS

Fluides aqueux

Huiles, hydrocarbures, peintures, adhésifs

Water-based fluids

Oil & Gas, paintings, adhesives

OPTIONS

Taroudage NPT / API

Clé sur demande



NPT / API connection

Handlever square on request