



AUTEXIER

MANUFACTURER OF INDUSTRIAL VALVES

93 Rue Louis Blanc - 02300 CHAUNY - FRANCE
Phone : +33 (0)3 23 52 02 86 Fax : +33 (0)3 23 39 52 28
Website : www.autexier.fr

Ref. 404 Family : 17

Rev. 05

Date : 17 Sept. 2025

Page 1/2

BRONZE CHECK VALVE TYPE VERTICAL LIFT Ref. 404AØ / 404TØ

SERIES :

- 404A : Contact Stainless steel / Stainless steel
- 404T : Contact Stainless steel / PTFE

For material compatibility, contact us



CARACTERISTICS :

- PN30 (Nominal Pressure)
- ENDS : BSP Female threads
- MATERIAL : BRONZE CC491K

MAXIMUM CONDITIONS OF USE :

- 30 bar of -45°C to 225°C

APPLICATIONS :


- Water-based fluids

Subject to modifications


OPTIONS :

- NPT/API connection
 - Stainless steel springloaded
- Specific dimensions, contact us*

NOMENCLATURE			
Rep	Qty	Designation	Material
1	1	BODY	BRONZE
2	1	BONNET	BRASS
4	1	DISC	PTFE/STAINLESS STEEL A1
5	1	DISC HOLDER	BRASS
6	1	SEAT	STAINLESS STEEL A1
9	1	BONNET NUT	BRONZE
38	1	SCREW (DN08 & DN12)	STAINLESS STEEL A4-70
40	1	NUT (DN15)	BRASS
41	1	WASHER (DN15)	BRASS



DN08 & DN12



REFERENCES NORMS :

- Material : NF EN 1982 - NF EN 12163 - NF EN 12164 - NF EN 10272
- Testing & checking : NF EN 12266-1/-2 (bench test)

Ref. instruction of assembling : 0904DA109E

Ref. instruction of operation : 0904DA110E

**Mounting & assembly guides are available
on our website.**

DIMENSIONS			
DN	08	12	15
A (mm)	52	58	65
D	1/4"	3/8"	1/2"
H (mm)	33	33	36
Weight (Kg)	0.300	0.350	0.450

These data are for information and can be modified without notice. It is not up to us to appreciate specifications. It is up to the customer to verify the adequacy between the equipment chosen and the real conditions of use.



AUTEXIER

MANUFACTURER OF INDUSTRIAL VALVES

93 Rue Louis Blanc - 02300 CHAUNY - FRANCE
Phone : +33 (0)3 23 52 02 86 Fax : +33 (0)3 23 39 52 28
Website : www.autexier.fr

Ref. 404 Family : 17

Rev. 05

Date : 17 Sept. 2025

Page 2/2

BRONZE CHECK VALVE TYPE VERTICAL LIFT Ref. 404AØ / 404TØ

SERIES :

- 404A : Contact Stainless steel / Stainless steel
 - 404T : Contact Stainless steel / PTFE
- For material compatibility, contact us



CHARACTERISTICS :

- PN30 (Nominal Pressure)
- ENDS : BSP Female threads
- MATERIAL : BRONZE CC491K

MAXIMUM CONDITIONS OF USE :

- 30 bar of -15°C to 200°C

APPLICATIONS :

- Water-based fluids


Subject to modifications

OPTIONS :

- NPT/API connection
 - Stainless steel springloaded
- Specific dimensions, contact us

NOMENCLATURE

Rep	Qty	Designation	Material
1	1	BODY	BRONZE
2	1	BONNET	BRONZE
4	1	DISC	PTFE / STAINLESS STEEL A1
5	1	DISC HOLDER	BRONZE
6	1	SEAT	STAINLESS STEEL A1
9	1	BONNET NUT	BRONZE
39	1	FIN (DN40 & DN50)	BRONZE
40	1	NUT (DN20 to DN32)	BRASS
41	1	WASHER (DN20 to DN32)	BRASS
45	1	O-RING	FPM



REFERENCES NORMS :

- Material : NF EN 1982 - NF EN 12163 - NF EN 12164 - NF EN 10272
- Testing & checking : NF EN 12266-1/-2 (bench test)

Ref. instruction of assembling : 0904DA109E

Ref. instruction of operation : 0904DA110E

**Mounting & assembly guides are available
on our website.**

DIMENSIONS

DN	20	25	32	40	50
A (mm)	84	98	110	120	145
D	3/4"	1"	1 1/4"	1 1/2"	2"
H (mm)	48	55	65	75	90
Weight (Kg)	0.850	1.300	1.950	3.000	4.350

These data are for information and can be modified without notice. It is not up to us to appreciate specifications. It is up to the customer to verify the adequacy between the equipment chosen and the real conditions of use.