



AUTEXIER

MANUFACTURER OF INDUSTRIAL VALVES

93 Rue Louis Blanc - 02300 CHAUNY - FRANCE
Phone : +33 (0)3 23 52 02 86 Fax : +33 (0)3 23 39 52 28
Website : www.autexier.fr

Ref. A3299 Family : 46

Rev. 00

Date : 28 July 2026

Page 1/1

BRONZE FIRE HYDRANT ANGLE VALVE Ref. A3299.Ø

SERIES :

- A3299.Ø

For material compatibility, contact us

CARACTERISTICS :

- PN16 (Nominal Pressure)
- ENDS : Inlet flange ISO PN16
BSP Threaded outlet
- MATERIAL : BRONZE CC491K

MAXIMUM CONDITIONS OF USE :

- 16 bar of -15°C to 100°C

APPLICATIONS :


- Fire networks
- Seawater

OPTIONS :

- Special drilling
 - Double tightness packing
- Specific dimensions, contact us*



Registered design by AUTEXIER Company
Subject to modifications



NOMENCLATURE			
Rep	Qty	Designation	Material
1	1	BODY	BRONZE
2	1	BONNET	BRONZE
4	1	DISC	NBR
5	1	DISC HOLDER	BRONZE
7	1	STEM	ALUMINIUM BRONZE
8	1	HANDWHEEL	EPOXY COATED ZAMAK/STEEL (DN65)
40a	1	NUT	STAINLESS STEEL ⁽²⁾
40b	1	NUT	STAINLESS STEEL ⁽²⁾
41a	1	WASHER	STAINLESS STEEL A4 / ALUMINIUM BRONZE (DN65)
41b	1	WASHER	STAINLESS STEEL A4
45a	1	O-RING / GASKET	FPM / ELASTOMER + FIBER (DN65)
45b	1	O-RING	FPM

REFERENCES NORMS :

- Material : NF EN 1982 - NF EN 12163 - NF EN 12164 - NF EN 10272
- Testing & checking : NF EN 12266-1/-2 (bench test)
- Thread : ISO 228-1
- Flange : NF EN 1092-3
- Stainless steel fasteners : ⁽¹⁾ NF EN ISO 3506-1/-2 (A4-70)
or NF EN 10269 (1.4404 or 1.4401) / ⁽²⁾ STAINLESS STEEL A4-70 or its equivalent

Ref. instruction of assembling : 0904DA119E

Ref. instruction of operation : 0904DA120E

**Mounting & assembly guides are available
on our website.**

These data are for information and can be modified without notice. It is not up to us to appreciate specifications. It is up to the customer to verify the adequacy between the equipment chosen and the real conditions of use.

DIMENSIONS				
DN	40	40 / 50	50	65
D (mm)	150	150	165	185
H (mm)	176	176	203	215
H' Maxi (mm)	210	210	235	260
h (mm)	66	66	74	82
b (mm)	16	16	18	17
L (mm)	78	78	84	80
O	G 1"1/2	G 2"	G 2"	G 2"1/2
P (mm)	18	18	19	19 / 22
V (mm)	110	110	110	150